



# ISMART CEILING DISPLAY

*Opening up new dimensions*



## UNIQUE FEATURES

### Only 28 mm Thick

Wrapped in an aluminum body and guarded by vandal-resistant safety glass, iSmart Display combines aesthetics and ruggedness.

### High-Quality Visual Rendering

Enhanced optical filters increase visibility and brightness of iSmart Display's high-resolution screens.

### Low Energy Consumption

Wabtec's unique backlight technology reduces the energy consumption of the iSmart Display by 45% in comparison to V-shaped displays, and increases its lifetime.

### Double Sided

Independent content on each display side.

The high definition iSmart Ceiling Display is the perfect companion for rich travel information. Its remarkably thin design provides an impression of lightness while being extremely robust.



The iSmart Display portfolio provides aesthetic design and high visual rendering through lean design, immersive experience, seamless integration and smart technology.

**PRODUCT'S LEVEL OF MATURITY**

Concept                      Under Development                      **Available**

**PRODUCT SPECIFICATION****TFT PANEL**

Technology	LCD TFT
Models	Model 42" - Full HD 41.5" 1/3 cut - Aspect ratio 32:6 Model 32" - Full HD 32.5" 1/2 cut - Aspect ratio 32:9 (Other size on request)
Maximum brightness	1000 cd/m <sup>2</sup> (typ.)
Brightness control	By ambient brightness
Contrast	3000:1 (typ.)
Viewing angle	Horizontal 178° (typ.), vertical 178° (typ.)
LED backlight lifetime	Standard: 100,000h Extended: 150,000h

**CONTROLLER**

Operating system	LINUX
Ethernet network	100 MBit/s
Protocols	VDV301, ITxPT, HTML, MQTT, SNMP, WebRTC, RTSP, TrainIT, TRDP (IEC61375-2-3), CIP, IPTCOM...

**HOUSING**

Enclosure material	Aluminum
Protection class acc. EN 60529	IP54
Front glass	Laminated safety glass 4.38 mm
Anti-reflection coating	Chemical or optical
Weight	14 kg

**OPERATION**

Temperature range in operation	EN 50155 OT3, -25 °C to +70 °C
Power supply	110 V DC, 72 V DC, 24 V DC

**STANDARDS**

Railway applications	EN 50155:2017
EMC	EN 50121-3-2:2015
Fire safety	EN 45545-2:2020-10

**CONTACT**

**Wabtec Corporation**  
 30 Isabella Street  
 Pittsburgh, PA 15212 - USA  
 Phone: 412.825.1000  
 Fax: 412.825.1019  
 Email: info.cctvpis@wabtec.com